

LT86121RX --- Product Brief

HDMI1.4 Repeater with DSC Decoder

Features

● HDMI1.4 Receiver

- Compliant with HDMI1.4 and DVI1.0
- No HDCP decryption
- Data rate up to 3Gbps
- Adaptive receiver equalization
- AC-couple capable
- Support channel swap(arbitrarily) and polarity inversion(independent)
- Support 4k@30Hz
- Supported 3D video
- 5V tolerance DDC/HPD I/Os
- Integrated EDID shadow
- 2/3 data channels option(2ch-to-3ch, paired with LT86121TX)
- Integrated DSC decoder(paired with LT86121TX)
- FEC support(paired with LT86121TX)

● HDMI1.4 Transmitter

- Compliant with HDMI1.4 and DVI1.0
- Compliant with HDCP1.4
- Data rate up to 3Gbps
- On-die back termination
- Programmable transmitter swing and pre-emphasis
- Support channel swap(arbitrarily) and polarity inversion(independent)
- Support 4k@30Hz
- Supported 3D video
- 5V tolerance DDC/HPD I/Os

● Digital Audio Input/Output

- I2S interface supporting 2-channel audio, with sample rates of 32~192 kHz and sample sizes of 16~24 bits
- SPDIF interface supporting PCM, Dolby Digital, DTS digital audio at up to 192kHz frame rate
- IEC60958 or IEC61937 compatible

● Miscellaneous

- Integrated USB HS/FS/LS repeater(paired with LT86121TX)
- CSC: RGB <-> YCbCr4:4:4 <-> YCbCr4:2:2
- Integrated CEC Controller
- External oscillator
- Integrated microprocessor
- Embedded SPI flash for firmware and HDCP keys
- GPIOs for system controls
- Integrated 100/400kHz I2C slave
- Firmware update through I2C interface
- Power supply: 3.3V for I/O and 1.2V for core
- ESD 4kV HBM
- Temperature Range: -40°C ~ +85°C
- Package: QFN76(9mm*9mm)

Description

The LT86121RX is a high performance HDMI1.4 repeater designed for long cable application. It should be paired with LT86121TX for longest cable reach. In paired mode, several unique features can be enabled to reduce bandwidth requirement and optimize performance.

Both the HDMI1.4 input and output support data rate up to 3Gbps which provides sufficient bandwidth for 4k@30Hz video. Also HDCP1.4 is supported for data encryption.

In paired mode, YCbCr4:1:1 conversion and DSC decoder can be used to reduce data rate and hence bandwidth requirement. Furthermore, FEC can be activated to correct data error and help to enhance system error tolerance level. These unique techniques together will significantly extend transmission distance. 2ch-to-3ch conversion eliminates the necessary of 3 differential data pairs as required by HDMI specification.

But data rate will increase by 50%. In applications of low and middle bandwidth, 2 data pairs are enough for data transmission.

Integrated USB repeater supports high speed, full speed and low speed modes. It is suitable for USB signal extension. User defined packet is also supported which

provides a path for sideband data communication.

The device is capable of automatic operation which is enabled by an integrated microprocessor that uses an embedded SPI flash for firmware storage. System control is also available through the configuration I2C slave interface.

Applications

- Active Cables
- Surveillance
- KVM Extension




Figure1. Application Diagram

Ordering Information

Part Number	Operating Temperature Range	Package	Packing Method
LT86121RX	-40°C to +85°C	QFN76 (9*9)	Tray

Copyright © 2018 Lontium Semiconductor Corporation, All rights reserved.

Lontium Semiconductor Proprietary & Confidential

This document and the information it contains belong to Lontium Semiconductor. Any review, use, dissemination, distribution or copying of this document or its information outside the scope of a signed agreement with Lontium is strictly prohibited.

LONTIUM DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THOSE OF NONINFRINGEMENT, MERCHANTABILITY, TITLE AND FITNESS FOR A PARTICULAR PURPOSE. CUSTOMERS EXPRESSLY ASSUME THEIR OWN RISK IN RELYING ON THIS DOCUMENT.

LONTIUM PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS WHERE A MALFUNCTION OF A LONTIUM DEVICE COULD RESULT IN A PERSONAL INJURY OR LOSS OF LIFE.

Lontium assumes no responsibility for any errors in this document, and makes no commitment to update the information contained herein. Lontium reserves the right to change or discontinue this document and the products it describes at any time, without notice. Other than as set forth in a separate, signed, written agreement, Lontium grants the user of this document no right, title or interest in the document, the information it contains or the intellectual property in embodies.

Trademarks

Lontium™ 龙迅™ and ClearEdge™ is a registered trademark of Lontium Semiconductor. All Other brand names, product names, trademarks, and registered trademarks contained herein are the property of their respective owners.

Visit our corporate web page at: www.lontiumsemi.com

Technical support: support@lontium.com

Sales: sales@lontium.com